



- Specification:
1. Rating : DC 25V 3A;
  2. Contact resistance :  $\leq 30\text{m}\Omega$  ;  
After test :  $\leq 50\text{m}\Omega$
  3. Insulation resistance :  $\geq 100\text{M}\Omega$  (500VDC) ;  
After test :  $\geq 50\text{M}\Omega$
  4. Withstanding voltage : 500VAC ;
  5. Insertion and extraction force : 3N~30N ;
  6. Life test : 5000cycles min ;
  7. Operation temperature range :  $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
  8. Preservative temperature range :  $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
  9. Key dimensions are marked as "★"

Model No.	DC044 SMT
Schematic	

设计:	Arvin: 2016.03.08	范围 Range	公差 Tolerance	东莞市恒祺电子科技有限公司	
审核:	Arvin:	X.X ±	X.X ±0.30		
校对:	Ru yi:	X.XX ±	X.XX ±0.20	名称: DC插座	型号: DC-044E
比例:	视角关系:	X.XXX ±	X.XXX ±0.10	料号:	
版次:	图框大小: A4	Angle ±	Angle ±5°	共 张 , 第 张	备注: